PHILIPPINE POSTAL CORPORATION

Agency or Office

	RFQ# 338-12-2	2			07-Dec-22	
	(Canvass Number	er)	•		(Date)	
			REQUEST FOR QUOTATION			
	(Name of Deale	r)	-			
	`	,				
			-			
	(Address)					
entlen	nen:					
rovider uotatio	rs/Suppliers to quote in duly signed by its	e their best of authorized re	n its Bids and Awards Committee - Alternative Methods of Procurement (E fer/price inclusive of all costs and applicable taxes, subject to the General presentative not later than <u>12</u> December 2022, 10:00AM at the Procurem ive, Liwasang Bonifacio, Ermita, Manila.	Conditions stated	herein, and to sub	omit the said
AME (OF PROJECT:		Procurement of UPS for Server			
eneral	I Conditions:					
1	All entries must be	typewritten o	r legibly written.			
2	required to be subr	mitted along v	Certificate/Number, Mayor's or Business Permit, Tax Clearance and Revis with your quotation/proposal on the date stated above. For Corporation or Special Power of Attorney to your designated Authorized Representative.	Partnership, please		
3			7) calendar days commencing on the date of receipt of PO/ Notice to Proc			
4	• •		working days from the date of submission of quotation/proposal.			
5			on completion and acceptance by PHLPost and the submission of the requ	uired supporting do	cuments.	
6 7	Quotations exceed Bidder/s shall indic	•	snall be rejected. ct, accurate and complete information including the BRAND NAME and M	ODEL NO of the o	ffered item(s) or r	product
8			marked quotation together with the documentary requirements.	3BEE 140. 01 tilo 0	norod norn(o) or p	oroddot.
			EAN DISQUALIFICATION OF YOUR PROPOSAL)			
			Very truly yours,			
			• • • •	C. MEDINA. JR.		
			ENGR. RICARDO	•		
IOTE:			• • • •	•		
IOTE:	ested by MISD		ENGR. RICARDO	•		
s requ	ested by MISD ABC (PhP)	Qty./ Unit	ENGR. RICARDO	•		ial Proposal
s reque Item No.	ABC (PhP)	ļ ·	ENGR. RICARDO A/Chief, Procurement	nt Division, LPMD	Unit Price	Total Amou
s requ		ļ ·	ENGR. RICARDO A/Chief, Procurement SPECIFICATIONS UPS for SERVER	•		
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications:	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	ENGR. RICARDO A/Chief, Procurement SPECIFICATIONS UPS for SERVER	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass,	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing)	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output:	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Power Factor 0.9	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Voltage Distortion (<3% @ 100% Linear Load)	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Power Factor 0.9	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Voltage Distortion (<3% @ 100% Linear Load) (<7% @ 100% Non-Linear Load) Output Voltage Regulation (±1%) Frequency Range (±1HZ or ±3HZ)	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Power Factor 0.9 Output Voltage Distortion (<3% @ 100% Linear Load) (<7% @ 100% Non-Linear Load) Output Voltage Regulation (±1%) Frequency Range (±1HZ or ±3HZ) Crest Factor 3:1	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Voltage 220/230/240 Vac Output Voltage Distortion (<3% @ 100% Linear Load) (<7% @ 100% Non-Linear Load) Output Voltage Regulation (±1%) Frequency Range (±1HZ or ±3HZ) Crest Factor 3:1 Output Waveform (Pure Sine Wave)	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Power Factor 0.9 Output Voltage Distortion (<3% @ 100% Linear Load) (<7% @ 100% Non-Linear Load) Output Voltage Regulation (±1%) Frequency Range (±1HZ or ±3HZ) Crest Factor 3:1	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Power Factor 0.9 Output Voltage Regulation (±1%) Frequency Range (±1HZ or ±3HZ) Crest Factor 3:1 Output Waveform (Pure Sine Wave) Efficiency: Line Mode Up to 92%, High Efficiency Mode Up to 97% Battery:	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	ļ ·	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Power Factor 0.9 Output Voltage Regulation (±1%) Frequency Range (±1HZ or ±3HZ) Crest Factor 3:1 Output Waveform (Pure Sine Wave) Efficiency: Line Mode Up to 92%, High Efficiency Mode Up to 97% Battery:	nt Division, LPMD	Unit Price	Total Amou
s requi	ABC (PhP) 270,000.00	6 pcs	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket - Standard RS-232, EPO Option USB, RS-485 (Modbus), Dry Contact Relay, SNMP/WEB Card Features: Display (LCD measures voltage, frequency, load level, battery level, output current, estimated autonomy, self-diagnostics upon power-on, front panel setting & software control, 24 hours routine check Alarm Audible or Visual Line Failure, Battery Low, Transfer to Bypass, System Fault) Full Protection Overload, Over temperature, Short Circuit, Discharge, Overcharge Multi-Mode Normal/ ECO/ CVCF Function, With DC start Input: Voltage Range 110~300Vac Frequency Range 45-65Hz (Auto Sensing) 100% Linear Load Output: Capacity - 3000VA/2700W Output Voltage 220/230/240 Vac Output Voltage 220/230/240 Vac Output Voltage Pistortion (<3% @ 100% Linear Load) (<7% @ 100% Non-Linear Load) Frequency Range (±1HZ or ±3HZ) Crest Factor 3:1 Output Waveform (Pure Sine Wave) Efficiency: Line Mode Up to 92%, High Efficiency Mode Up to 97% Battery: Capacity 2Vdc/9Ah 6 Battery, 72 Voltage Battery	nt Division, LPMD	Unit Price	Total Amou
s reque Item No.	ABC (PhP)	6 pcs	SPECIFICATIONS UPS for SERVER Specifications: Interface: - 6 x IEC-C13 Sockets, 1 x IEC-C19 Socket	Comply	Unit Price	Total Amou

(Telephone Number)

RFQ# 338-12-22

Option: ____

Accredited Manufacturer/Supplier may personally obtain the specifications on the canvass forms from the **PROCUREMENT DIVISION**, **Logistics and Property Management Department**, **4**th **Floor**, **Manila Central Post Office Main Building** on the day following the date of this invitation.

The Philippine Postal Corporation reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with section 41 of RA 9184 and its IRR, without thereby incurring any bidder liability to the affected bidder or bidders.

FOR FURTHER INFORMATION, PLEASE GET IN TOUCH WITH THE PROCUREMENT DIVISION, LPMD at TELEPHONE NUMBERS 8527-01-33